SIEMENS

Show actual product details

Data sheet 6GK1905-0AA00

Product type designation

SpliT Connect Tap

PROFIBUS PA SPLITCONNECT TAP, FOR ASSEMBLING OF PROFIBUS PA SEGMENTS AND CONNECTION OF PA FIELD DEVICES, INSULATION DISPLACEMENT TERMINAL, IP67 PACK. UNIT: 10 PIECES = 1 PACK



Electrical data	
Transfer rate / with PROFIBUS PA	31.25 kbit/s
Interfaces	
Number of electrical connections	
• for PROFIBUS cables	3
Type of electrical connection	
• for PROFIBUS cables	integrated insulation displacement contacts
Mechanical data	
Material / of the enclosure	PBT (polybutyleneterephthalate)
Design, dimensions and weight	
Width	84 mm
Height	54 mm
Depth	49 mm
Net weight	170 g
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Subject to change without notice
© Copyright Siemens AG

Permitted ambient conditions	
Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Protection class IP	IP67

Standards, specifications, approvals	
Certificate of suitability	
• UL approval	Yes

Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 07/08/2016

Subject to change without notice
© Copyright Siemens AG