SIEMENS

Data sheet 6ES7143-4BF50-0AA0



SIMATIC DP, Electronic modules for ET 200 PRO 4 DI/4 DO 24 V DC, 0.5A Module diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately

Supply voltage	
Load voltage 2L+	
● Rated value (DC)	24 V
● Short-circuit protection	Yes
● Reverse polarity protection	Yes
Input current	
from load voltage 2L+ (without load), max.	20 mA
from backplane bus 3.3 V DC, max.	20 mA
Encoder supply	
Short-circuit protection	Yes; per module, electronic
Output current	
● up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	2 W
Digital inputs	
Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-3 to +5V
● for signal "1"	+11 to +30V
Input current	
● for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	3 ms
— at "1" to "0", max.	3 ms
Cable length	
● unshielded, max.	30 m
Digital outputs	
Number of digital outputs	4
Short-circuit protection	Yes; per channel, electronic
● Response threshold, typ.	0.7 A
Limitation of inductive shutdown voltage to	Typ. (2L+) -47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
● on lamp load, max.	5 W
Load resistance range	
● lower limit	48 Ω
● upper limit	4 kΩ

Subject to change without notice
© Copyright Siemens

Output current	
● for signal "1" rated value	0.5 A
● for signal "0" residual current, max.	0.5 mA
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	0.5 Hz
● on lamp load, max.	1 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 55 °C, max.	2 A
Cable length	
● unshielded, max.	30 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Diagnostic information readable	Yes
● Short-circuit	Yes; Short-circuit of outputs to ground; module by module
Diagnostics indication LED	
● Status indicator digital input (green)	Yes
● Status indicator digital output (green)	Yes
Potential separation	
between backplane bus and all other circuit components	Yes
Potential separation digital inputs	
● between the channels	No
● between the channels and backplane bus	Yes
Potential separation digital outputs	
● between the channels	No
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	140 g

last modified: 8/23/2023

Subject to change without notice
© Copyright Siemens