SIEMENS

Data sheet 6ES7922-3BD00-0AS0

S7-300 FRONT CONN. 40 TO DB50F 3M
Cable with front connector for SIMATIC S7-300 40-pole (6ES7392-1AM00-0AA0) on 50 pole D-sub socket for ET 200M; 0.14 mm2
Length = 3 m

target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA

Product properties, functions, components / general / header	
wire length	3 m
design of cable	Round cable
material / of the connecting cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	9.8 mm; bundled single cores
conductor cross section / rated value	0.5 mm²
number of channels	40
number of poles	40; of the front connector

Operating data / header	
operating voltage / at DC	
• rated value	24 V
• maximum	30 V
ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C

General data / header	
certificate of suitability / cULus approval	No
suitability for interaction	
• input card PLC	Yes
• PLC output card	Yes
suitability for use	
• digital signal transmission	Yes
• analog signal transmission	Yes
type of electrical connection	
• in the field	Connector strip
• on enclosure	Screw-type terminal
reference code / acc. to DIN EN 81346-2	W
net weight	0.678 kg

Subject to change without notice
© Copyright Siemens