SIEMENS

Data sheet 6ES7132-6FD00-0CU0



SIMATIC ET 200SP, digital output module DQ 4x 24..230V AC/2A HF packaging unit: 1 piece, two alternative modes: DQ and power control, fits to BU-Type U0, color code CC20, channel diagnosis

General information	
Product type designation	DQ 4x24 ... 230 V AC/2 A HF
HW functional status	From FS03
Firmware version	
● FW update possible	Yes
usable BaseUnits	BU type U0
Color code for module-specific color identification plate	CC20
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V14
● STEP 7 configurable/integrated from version	STEP 7 V5.5 or higher
● PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● DQ	Yes
● DQ with energy-saving function	Yes
● PWM	No
● Oversampling	No
● MSO	No
● Phase control	Yes; Control area: 8.5 ... 100% of the phase angle
● Trailing-edge phase	No
● Half-wave	Yes
● Full-wave	Yes
Supply voltage	
Rated value (AC)	230 V; 47 ... 63 Hz, max. rate of change of frequency 1 mHz/s
permissible range, lower limit (AC)	20.4 V
permissible range, upper limit (AC)	264 V
Input current	
Current consumption (rated value)	8 mA; without load
output voltage / header	
Rated value (AC)	230 V; 24V AC to 230V AC
Power loss	
Power loss, typ.	9 W; Active power, load voltage 230 V, all outputs loaded with 2 A, 50 Hz
Address area	
Address space per module	
● Inputs	+ 1 byte for QI information
● Outputs	8 byte
Hardware configuration	

Subject to change without notice
© Copyright Siemens

Automatic encoding	Yes
● Mechanical coding element	Yes
● Type of mechanical coding element	type C
Selection of BaseUnit for connection variants	
● 1-wire connection	BU type U0
● 2-wire connection	BU type U0
● 3-wire connection	BU type U0 + Potential distributor module
Digital outputs	
Type of digital output	Triac
Number of digital outputs	4
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No; external fusing necessary
Open-circuit detection	Yes; channel by channel
● Response threshold, typ.	1 mA; 40 V AC or more
Overload protection	No; A miniature fuse with 10 tripping current and tripping characteristic "quick response" must be provided in the module supply
Controlling a digital input	Yes
Switching capacity of the outputs	
● with resistive load, max.	2 A; Max. 4 A, see additional description in manual
● with inductive load, max.	2 A
● on lamp load, max.	100 W; Tungsten rating in accordance with UL; for thermistors with higher power ratings, see the notes in the manual
Output voltage	
● for signal "1", min.	20.4 V
Output current	
● for signal "1" rated value	2 A
● for signal "1" permissible range, min.	10 mA
● for signal "1" permissible range, max.	4 A; note derating data in the manual
● for signal "0" residual current, max.	3 mA
Output delay with resistive load	
● "0" to "1", max.	40 ms; 2 AC cycles
● "1" to "0", max.	20 ms; 1 AC cycle
Parallel switching of two outputs	
● for logic links	No
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	10 Hz; Applies to DQ mode; limited by line frequency in PC mode
● with inductive load (acc. to IEC 60947-5-1, AC15), max.	10 Hz; Applies to DQ mode; limited by line frequency in PC mode
● on lamp load, max.	1 Hz; Applies to DQ mode; limited by line frequency in PC mode
Total current of the outputs	
● Current per channel, max.	2 A; Max. 4 A, see additional description in manual
● Current per module, max.	8 A
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	8 A
— up to 50 °C, max.	6 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	6 A
— up to 50 °C, max.	4 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	

Subject to change without notice
© Copyright Siemens

● Diagnostic alarm	Yes
Diagnoses	
● Diagnostic information readable	Yes
● Monitoring the supply voltage	Yes
● Wire-break	Yes; channel by channel
● Short-circuit	No
● Group error	Yes
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red Fn LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	2 545 V DC/2 s (routine test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	50 g

last modified: 8/16/2023

Subject to change without notice
© Copyright Siemens