SIEMENS

Data sheet 3WL9111-0AD02-0AA0

accessories circuit breaker 3WL shunt trip DC 30V, 100% ed

Model	
Product brand name	SENTRON
General technical data	
Closing apparent power [VA]	15 V·A
Closing active power [W]	15 W
Minimum command time / at Us = 100%	60 ms
Make time / electrical	100 ms
Opening time / of circuit breaker / at Us = 100%	80 ms
Voltage	
Surge voltage resistance	4 kV
Adjustable parameters	
Response value	
• of pick-up voltage / minimum	0.7
Connections	
Connectable conductor cross-section	
• minimum	0.5 mm²
• maximum	1.5 mm²
AWG number / as coded connectable conductor cross section / for auxiliary contacts	
• minimum	20
• maximum	16
Environmental conditions	
Ambient temperature / during operation	
• minimum	-40 °C
• maximum	70 °C
Ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
Certificates	

Subject to change without notice
© Copyright Siemens

Declaration of Conformity	Test Certificates	Shipping Approval	other		
EG-Konf.	Miscellaneous	RMRS	Environmental Confirmations	Manufacturer Declaration	Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AD02-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AD02-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0AD02-0AA0

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens