SIEMENS

Data sheet 6AG1900-0AB00-7AA0

SIPLUS NET C-Plug -40...+70°C with conformal coating based on 6GK1900-0AB00 . removable data storage medium for simple Replacement of devices in case of failure for recording configuration or project engineering and application data, Can be used in SIMATIC NET products with C-Plug slot



Figure similar

ambient conditions	
ambient temperature	
• in horizontal mounting position / during operation	-40 ... +75 °C
• during storage and transport	80 ... -40 °C
installation altitude / at height above sea level / maximum	5000 m
relative humidity	
• with condensation / acc. to IEC 60068-2-38 / maximum	100 %
resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes
resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes
resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes
protection class IP	IP20

Subject to change without notice
© Copyright Siemens

standards, specifications, approvals

reference code	
• according to IEC 81346-2:2019	CFA

further information / internet-Links

Internet-Link	
• to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to the website: IWLAN	http://www.siemens.com/iwlan
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	11/23/2020

Subject to change without notice
© Copyright Siemens