SIEMENS

Data sheet 8WD4428-6XF

LED, Base BA 15d, blue, 24 V AC/DC, accessory for signaling columns, with diameters 50 mm and 70 mm



General technical data	
product brand name	SIRIUS
product designation	LED
type of voltage of the operating voltage	AC/DC
operating voltage	
• 1 at DC rated value	24 V
• 1 at AC at 50 Hz rated value	24 V
• 1 at AC at 60 Hz rated value	24 V
relative positive tolerance of the operating voltage	10 %
relative negative tolerance of the operating voltage	-15 %
consumed current maximum	15 mA
color	blue
reference code	
• acc. to DIN EN 61346-2	P
• acc. to DIN EN 81346-2	P

Mechanical data	
outer diameter of the signal column element	70 mm

Lamp

Subject to change without notice
© Copyright Siemens

type of light source	LED
light intensity	0.21 cd
mounting type	BA 15d

Ambient conditions

ambient temperature during operation	-20 ... +60 °C
height	45 mm
width	20 mm

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity	other	
UL	RCM	EG-Konf.	Miscellaneous	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4428-6XF

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4428-6XF

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/8WD4428-6XF

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4428-6XF&lang=en

last modified: 09/24/2020

Subject to change without notice
© Copyright Siemens