SIEMENS

Data sheet for Absolute encoder



Figure similar

MLFB-Ordering data **6FX2001-5FN25**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data

Operating voltage Up	DC 10 ... 30 V
Max. power consumption	130 ... 400 mA (< 4 W)
Interface	PROFINET IO with RT / IRT
Clock input	2 ports IRT
Data output	2 ports IRT
Short-circuit strength	Yes
Transmission rate	100 Mbit/s
LED for diagnostics	Yes (green/red/yellow)
Connection type	2 x connector M12, 4-pin for PROFINET / EtherNet/IP Ports, 1 x connector M12, 4-pin for operating voltageRadial
Resolution	27 bit (8192 increments x 16384 rpms)
Telegram	According to PNO cncoder profile V4.1 Class1, Class 2, Class 3, Class 4, standard telegrams 81/82/83/84, Siemens telegram 860

Code type

Sampling	Gray
Transmission	binary, PROFINET / EtherNet/IP

Cable length up to the subsequent electronics, max.

Up to 12 Mbit/s	100 m

Mechanical data

Shaft version	Solid shaft
Shaft diameter	6 mm
Shaft length	10 mm
Angular acceleration, max.	100000 rad/s²
Moment of inertia of rotor	0.00000301 kgm²
Vibration (55...2000 Hz), max.	100 m/s²
Friction torque (at 20°C)	<= 0.01 Nm
Starting torque (at 20°C)	<= 0.01 Nm
Net weight	0.4 kg

Speed max.

With ± 1 bit accuracy	5800 rpm
Max. permissible speed (mech.)	6000 rpm

Load capacity

n = 6000 rpm	
- Axial	10 N
- Radial at shaft end	20 N
n > 6000 rpm	
- Axial	40 N
- Radial at shaft end	110 N

Shock, max.

2 ms	2000 m/s²
6 ms	1000 m/s²

Degree of protection

Without shaft input	IP67
With shaft input	IP64

SIEMENS

Data sheet for Absolute encoder

MLFB-Ordering data **6FX2001-5FN25**



Figure similar

Electrical data

Parameterizability

Preset	Yes
Counting direction	Yes
Resolution per revolution	Any 1 ... 8192
Total resolution	Any 1 ... 8192
Speed signal	Yes
Limit switch	No
Clock synchronism	Yes
Slave-to-slave communication	No
Accuracy	± 79 " with 8192 increments (± 1/2 LSB)

Ambient temperature

During operation	-40 ... 85 °C

Standards

Compliance with standards	CE, cULus
EMC class filter	Tested to DIN EN 50081 and EN 50082