SIEMENS

Data sheet 6GT2398-1CD30-0AX0

Product type designation

Antenna ANT 3

RF300/RF200 antenna ANT 3 for Connection to RF250R RF350R and RF350M IP67. -25 to +70 °C, Dimensions 50x 28x 10 mm



Suitability for operation	RF250R / RF350R / RF350M
Radio frequencies	
Transmission frequency / Rated value	13.56 MHz
Electrical data	
Type of electrical connection / of the antenna	M8, 4-pin
Design of plug-in connection	female
Mechanical data	
Material	PA6 V0
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance	
• relating to metal surfaces / recommended / minimum	0 m
Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C

Subject to change without notice
© Copyright Siemens

• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Protection class IP	IP67
Shock resistance	according to EN 60721-3-7 Class 7M2
Shock acceleration	500 m/s²
Vibrational acceleration	200 m/s²

Design, dimensions and weights

Width	28 mm
Height	50 mm
Depth	10 mm
Net weight	35 g
Mounting type	2 x M4 screws

Standards, specifications, approvals

Certificate of suitability	CE, FCC, IC, cULus
Certificate of suitability	
• IECEx	Yes

accessories

accessories	Antenna cable

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 05/12/2020

Subject to change without notice
© Copyright Siemens