SIEMENS

Data sheet 3RK1301-0KB00-0AA2

DS1-X for ET 200S Standard DOL starter expandable Setting range 0.9...1.25 A AC-3, 0.37 kW / 400 V Electromechanical starter for brake control module



Figure similar

Product brand name	SIMATIC
Product designation	Motor starters
Design of the product	direct starter
Product type designation	ET 200S

General technical data	
Trip class	CLASS 10
Product function	
• on-site operation	Yes
Power loss [W] for rated value of the current	
• at AC in hot operating state	10 W
• at AC in hot operating state per pole	3.33 W
Power loss [W] for rated value of the current without load current share typical	4.12 W
Insulation voltage	
• rated value	500 V
Degree of pollution	3 at 400 V, 2 at 500 V according to IEC60664 (IEC61131)
Surge voltage resistance rated value	6 kV

Subject to change without notice
© Copyright Siemens

maximum permissible voltage for safe isolation	
• between main and auxiliary circuit	400 V
Protection class IP	IP20
Shock resistance	5g / 11 ms
Vibration resistance	2g
Operating frequency maximum	750 1/h
Mechanical service life (switching cycles)	
• of the main contacts typical	100 000
Type of assignment	2
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	A
Reference code acc. to DIN EN 81346-2	Q
Reference code acc. to DIN EN 61346-2	Q
Product function	
• direct start	Yes
• reverse starting	No
Product component Motor brake output	Yes
Product feature	
• brake control with 230 V AC	No
• brake control with 24 V DC	No
• brake control with 180 V DC	No
• brake control with 500 V DC	No
Product extension braking module for brake control	Yes
Product function Short circuit protection	Yes
Design of short-circuit protection	circuit-breakers
Maximum short-circuit current breaking capacity (Icu)	
• at 400 V rated value	50 kA

Electromagnetic compatibility

EMC emitted interference	
• acc. to IEC 60947-1	CISPR11, ambience A (industrial sector)
EMI immunity acc. to IEC 60947-1	corresponds to degree of severity 3, ambience A (industrial sector)
Conducted interference	
• due to burst acc. to IEC 61000-4-4	2 kV on voltage supply, inputs and outputs
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV (U > 24 V DC)
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV (U > 24 V DC)
Field-bound parasitic coupling acc. to IEC 61000-4-3	80 MHz ... 1 GHz 10 V/m, 1.4 GHz ...2 Hz 3 V/m, 2 GHz ... 2.7 GHz 1 V/m

Safety related data

B10 value	
• with high demand rate acc. to SN 31920	1 000 000

Subject to change without notice
© Copyright Siemens

Proportion of dangerous failures	
• with low demand rate acc. to SN 31920	50 %
• with high demand rate acc. to SN 31920	75 %
Failure rate [FIT]	
• with low demand rate acc. to SN 31920	100 FIT
T1 value for proof test interval or service life acc. to IEC 61508	20 y
Protection against electrical shock	finger-safe

Main circuit

Number of poles for main current circuit	3
Design of the switching contact	electromechanical
Adjustable pick-up value current of the current-dependent overload release	0.9 ... 1.25 A
Type of the motor protection	bimetal
Operating voltage	
• rated value	200 ... 400 V
Operating frequency 1 rated value	50 Hz
Operating frequency 2 rated value	60 Hz
Relative positive tolerance of the operating frequency	10 %
Relative negative tolerance of the operating frequency	10 %
Operating range relative to the operating voltage at AC	
• at 50 Hz	200 ... 440 V
Operating current	
• at AC-3	
— at 400 V rated value	1.25 A
Operating power	
• at AC-3	
— at 400 V rated value	0.37 kW
Operating power for three-phase motors at 400 V at 50 Hz	0.37 ... 0.37 kW

Inputs/ Outputs

Product function	
• digital inputs parameterizable	No
• digital outputs parameterizable	No
Number of digital inputs	0
Number of sockets	
• for digital output signals	0
• for digital input signals	0

Supply voltage

Type of voltage of the supply voltage	DC

Subject to change without notice
© Copyright Siemens

Supply voltage 1 at DC	24 ... 24 V
Supply voltage 1 at DC rated value	
• minimum permissible	20.4 V
• maximum permissible	28.8 V

Control circuit/ Control

Type of voltage of the control supply voltage	DC
Control supply voltage at DC	
• rated value	20.4 ... 28.8 V
Control supply voltage 1	
• at DC rated value	20.4 ... 28.8 V
• at DC	24 ... 24 V
Power loss [W] in auxiliary and control circuit	
• **in switching state OFF**	
— with bypass circuit	0.3744 W
— without bypass circuit	0.374 W
• **in switching state ON**	
— with bypass circuit	4.1184 W
— without bypass circuit	4.118 W

Installation/ mounting/ dimensions

Mounting position	vertical, horizontal
Mounting type	pluggable on terminal module
Height	265 mm
Width	45 mm
Depth	120 mm

Ambient conditions

Installation altitude at height above sea level	
• maximum	2 000 m
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity during operation	5 ... 95 %

Communication/ Protocol

Protocol is supported	
• PROFIBUS DP protocol	Yes
• PROFINET protocol	Yes
Design of the interface	
• PROFINET protocol	Yes
Product function Bus communication	Yes
Protocol is supported	
• AS-Interface protocol	No

© Copyright Siemens

Product function	
• supports PROFIenergy measured values	No
• supports PROFIenergy shutdown	No
address range memory of address range	
• of the inputs	1 byte
• of the outputs	1 byte
Type of electrical connection	
• of the communication interface	via backplane bus
• for communication transmission	via backplane bus

Connections/ Terminals

Type of electrical connection	
• for main current circuit	screw-type terminals
Type of electrical connection	
• 1 for digital input signals	using control module
• 2 for digital input signals	using control module
Type of electrical connection	
• at the manufacturer-specific device interface	plug
• for main energy infeed	screw-type terminals
• for load-side outgoing feeder	Screw-type terminals
• for main energy transmission	via energy bus
• for supply voltage line-side	via backplane bus
• for supply voltage transmission	via backplane bus

UL/CSA ratings

Operating voltage	
• at AC at 60 Hz acc. to CSA and UL rated value	600 V

Certificates/ approvals

General Product Approval				EMC	For use in hazardous locations
CCC	CSA	UL		RCM	ATEX

Declaration of Conformity		Test Certificates	other
EG-Konf.	Miscellaneous	Type Test Certificates/Test Report	Confirmation

Subject to change without notice
© Copyright Siemens

Further information


Information- and Downloadcenter (Catalogs, Brochures,…)
www.siemens.com/ic10


Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1301-0KB00-0AA2

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1301-0KB00-0AA2


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1301-0KB00-0AA2

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1301-0KB00-0AA2&lang=en





© Copyright Siemens



last modified: 05/15/2020

Subject to change without notice
© Copyright Siemens