SIEMENS

Data sheet 6ES7922-3BD01-0AM0

S7-300 FRONTSTECKER 20 TO DB25F 3M NEU

Cable with front connector for SIMATIC S7-300 20 pole (6ES7392-1AJ00-0AA0) on 25 pole D-SUB socket for ET200M; 0.14 mm2 Length = 3 m

target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA
Product properties, functions, components / general / header	
wire length	3 m
design of cable	Round cable
material / of the connection cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	7.6 mm; bundled single cores
conductor cross section / rated value	0.5 mm²
number of channels	20
number of poles	20; of the front connector
Operating data / header	
operating voltage / at DC	
● rated value	24 V
● maximum	30 V
ambient temperature	
● during storage	-30 ... +70 °C
● during operation	0 ... 60 °C
General data / header	
certificate of suitability / cULus approval	No
suitability for interaction	
● input card PLC	Yes
● PLC output card	Yes
suitability for use	
● digital signal transmission	Yes
● analog signal transmission	Yes
type of electrical connection	
● in the field	Connector strip
● on enclosure	Screw-type terminal
reference code / according to IEC 81346-2	WG
net weight	0.42 kg

Subject to change without notice
© Copyright Siemens