SIEMENS

Data sheet 6ES7143-5AH00-0BL0



SIMATIC ET 200AL, IO-Link, DIQ 16x24 V DC/0.5 A, 8x M12, Degree of protection IP67

General information	
Product type designation	IO-Link DIQ 16x24VDC/0.5A
HW functional status	FS01
Firmware version	V1.0.x
Vendor identification (VendorID)	42
Device identifier (DeviceID)	229383
Engineering with	
● IODD file	Yes
Supply voltage	
Load voltage 1L+	
● Rated value (DC)	24 V; Supply from 1Us+ of the IO-Link master
● permissible range, lower limit (DC)	18 V
● permissible range, upper limit (DC)	30 V
● Reverse polarity protection	Yes; against destruction
Load voltage 2L+	
● Rated value (DC)	24 V; Supply from 2UA+ of the IO-Link master
● permissible range, lower limit (DC)	20.4 V
● permissible range, upper limit (DC)	28.8 V
● Reverse polarity protection	Yes; Against destruction; encoder power supply outputs applied with reversed polarity, loads pick up
Input current	
Current consumption (rated value)	20 mA; without load
from load voltage 2L+, max.	4 A; Maximum value
Encoder supply	
Number of outputs	8; Supply from 2UA+ of the IO-Link master
24 V encoder supply	
● Short-circuit protection	Yes; per module, electronic
● Output current, max.	0.7 A; Total current of all encoders (depending on IO-Link master supply via 2UA+)
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	16; Parameterizable as DIQ
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	16
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-3 to +5V

Subject to change without notice
© Copyright Siemens

● for signal "1"	+11 to +30V
Input current	
● for signal "1", typ.	3 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
Cable length	
● unshielded, max.	30 m
Digital outputs	
Number of digital outputs	16; Parameterizable as DIQ
Short-circuit protection	Yes; per channel, electronic
● Response threshold, typ.	0.7 A
Limitation of inductive shutdown voltage to	2L+ (-50 V)
Switching capacity of the outputs	
● on lamp load, max.	5 W
Load resistance range	
● lower limit	48 Ω
● upper limit	4 kΩ
Output voltage	
● for signal "1", min.	L+ (-0.8 V)
Output current	
● for signal "1" rated value	0.5 A
● for signal "0" residual current, max.	0.5 mA
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	0.5 Hz
● on lamp load, max.	1 Hz
Total current of the outputs	
● Current per module, max.	4 A
Cable length	
● unshielded, max.	30 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
IO-Link	
IO-Link protocol 1.1	Yes
Transmission rate	38.4 kBd (COM2)
Cycle time, min.	3 ms
Size of process data, input per module	2 byte
Size of process data, output per module	2 byte
Supported IO-Link profiles	common profile
Cable length unshielded, max.	20 m
Connection of IO-Link devices	
● Port type B	Yes
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; channel by channel, parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable
Diagnoses	
● Short-circuit	Yes; outputs to ground; encoder supply to ground; module by module
Diagnostics indication LED	
● Channel status display	Yes; green LED
● for module diagnostics	Yes; green/red LED
● For load voltage monitoring	Yes; green LED
Potential separation	
between the load voltages	Yes

Subject to change without notice
© Copyright Siemens

Potential separation channels	
● between the channels	No
● between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; From FS01
Highest safety class achievable for safety-related tripping of standard modules	
● Performance level according to ISO 13849-1	PL d
● Category according to ISO 13849-1	Cat. 3
● SIL acc. to IEC 62061	SIL 2
Ambient conditions	
Ambient temperature during operation	
● min.	-30 °C
● max.	55 °C
connection method	
Design of electrical connection for the inputs and outputs	M12, 5-pin, A-coded
Type of electrical connection for IO-Link	M12, 5-pin, A-coded
Dimensions	
Width	45 mm
Height	159 mm
Depth	40 mm
Weights	
Weight, approx.	157 g

last modified: 8/16/2023

Subject to change without notice
© Copyright Siemens